

## Cibes A6000 - technical overview

|  |  |
|--|--|
| Lift location                          | Indoors  |
| Rated load                             | 400 kg   |
| Rated Speed (m/sec)                    | max 0,15   |
| Travel height                          | < 13 m   |
| Min.headroom at top landing            | 2700 mm  |
| Pit depth                              | 70 mm  |
| Flooring                               | Altro Walkway Plus™ 20/Dark Grey                                     |
| Cabin size (WxDxH)                     | 1100x1400x2200   |
| Min dimension shaft single entry (WxD) | 1530x1670 mm   |
| Min dimension shaft open through (WxD) | 1530x1780 mm   |
| Maximum number of stops                | 6  |
| Standard cabin finish                  | Steel panels, white RAL 9016   |
| Landing door                           | Telescopic, RAL 9016   |
| Cabin door                             | Telescopic, RAL 9016   |
| Landing door measurement               | 900x2100 mm  |
| Light curtain                          | Between cabin door and landing door                                  |
| Cabin door measurement                 | 900 x 2100 mm  |
| Driving system                         | Screw and nut  |
| Control system                         | CANbus microcomputer system  |
| Standard power supply                  | 3x400VAC/3x230VAC 50/60 Hz 16 A                                      |
| Motor power                            | 4 KW   |
| Control buttons                        | Impuls control   |
| Machine room                           | Integrated   |
| In compliance with                     | European MD 2006/42/EC and applicable parts of EN 81-41 and EN 81-70 |
| Manufactured in                        | Sweden   |